

WOOD MASTIC® BI Fast Powder

Bi-Component – Fast curing 40min

Use:

Wood Mastic® Fast Powder allows you to, for a record time, refill (up to 7 mm depth) on all vertical and horizontal wood used inside.

Characteristics:

First two-component mixing with water, **Wood Mastic® Fast Powder** can be sawed, nailed, screwed, pumiced, waxed, varnished and vitrified like wood and allows perfect recovery of hues. It provides a repair lasts, easy to sand which does not clog the abrasive strips.

Wood Mastic® Fast Powder is available in light wood, blond wood, dark wood and exotic wood.

Preparation:

Make sure before application that the surface is clean and dry. If necessary sand the wood or use the **Remover Odorless Briançon**. Thorough dusting.

Application:

Choose the closest shade of **Wood Mastic® Fast Powder** to the final color desired.

Mix 3 doses of powder and 1 dose of water. Knead the putty then leave it for a few minutes. The product, once prepared, can be preserved for 40 minutes.

Fill up and smooth in one operation repairs up to 7 mm depth. Beyond that, proceed in 2 successive passes.

When dry, sand lightly to get a perfect finish.

Technical data:

- Operating temperature: above 12 ° C.
- Wood humidity: between 8% and 12%.
- Hardening before sanding: between 30 minutes and 4 hours depending on the size of the repair
- Full cure: 24 hours
- Pot life of the mixture: 40 minutes
- Hardness shore A: 60
- Very economical Yield: 500g of powder used to obtain 650 g of mastic
- Storage: Store away from moisture.

Cleaning utensils:

Immediately after use and with water. Close the container after use. Place the empty container in waste. It will be necessary to contact the local authorities for the disposal and collection procedures. Do not discharge into drains.