

# WOOD MASTIC® P340 Classic Powder

**Bi-Component – Good adhesion**

**Use:**

**Wood Mastic® Classic Powder** allows you to refill big holes (up to 7 mm depth) on all vertical and horizontal wood used inside.

**Characteristics:**

First two-component mixing with water, **Wood Mastic® Classic Powder** can be sawed, nailed, screwed, pumiced, waxed, varnished and vitrified like wood and allows perfect recovery of hues.

It provides a repair that last longer, easy to sand which does not clog the abrasive strips.

**Wood Mastic® Classic Powder** is available in light wood, blond wood, dark wood and exotic wood.

**Preparation:**

Make sure before application that the surface is clean and dry. If necessary sand the wood or use the **Remover Odorless Briançon**.

Thorough dusting.

**Application:**

Choose the closest shade of **Wood Mastic® Classic Powder** to the final color desired.

Mix 3 doses of powder and 1 dose of water. Knead the putty then leave it for 15 minutes. The product, once prepared, can be preserved for 48 hours.

Fill up and smooth in one operation repairs up to 7 mm depth. Beyond that, proceed in 2 successive passes.

When dry, sand lightly to get a perfect finish.

**Technical data:**

- Operating temperature: above 12 ° C.
- Wood humidity: between 8% and 12%.
- Hardening before sanding: 40 minutes
- Full cure: 24 hours
- Pot life of the mixture: 36 hours
- Hardness shore A: 63
- Very economical Yield: 500g of powder used to obtain 650 g of mastic
- Storage: Store away from moisture.

**Cleaning utensils:**

Immediately after use and with water.

Close the container after use. Place the empty container in waste. It will be necessary to contact the local authorities for the disposal and collection procedures. Do not discharge into drains.

Technical sheet released on 05.19.2016. Designed, developed and manufactured in France. The information provided in this data sheet are given in good faith for guidance. They do not in any case induce a guarantee from us, or engage our responsibility when using our products. Refer to the Material Safety Data Sheet (MSDS) (available on [www.quickfds.com](http://www.quickfds.com)).